



## ORO<sub>2</sub><sup>TM</sup> Flow Control Valves

Spiracle Technology offers precision fixed orifice flow control with the ORO<sub>2</sub><sup>TM</sup> Flow Control Valve.

The unique 12 position flow control valve with its all metal construction is designed and built to work from hospital environments to out in the field EMS. The newest innovation in constant flow control is offered with 12 flow rate selections and is easy-to-read because the number is always in the 12 o'clock position, larger and can be seen in dimly lit environments.

The Mini-Manager and Multi-Manager O<sub>2</sub> Administrators <sup>TM</sup> feature 5 and 8 ORO<sub>2</sub><sup>TM</sup> Flow Control Valves manifolded together. The Multi-Manager is mounted to a compact, lightweight, aluminum alloy tripod. Offering a greater range of versatility and expandable systems, the Mini-Manager and Multi-Manager O<sub>2</sub> Administrators <sup>TM</sup> require less space to store and are ideal for mass casualty and military applications.

## 10 Good Reasons To Use Spiracle Technology Flow Control Valve

**Affordably Priced** – Affordable high quality craftsmanship will provide years of dependable and reliable service.

**All Metal Materials** – The all metal flow control valves are durable and lightweight.

**Precision Flow** – The accuracy of the whole number flow readings is plus or minus 10%.

**Increased Number of Flow Selections** – The 12 position flow control settings range from the OFF position to ¼, ½, 1, 2, 3, 4, 6, 8, 10, 15 and 25 liters per minute.

**Easy-to-Read** – The liters per minute flow rate setting is always in the 12 O'clock position and is the only number visible, eliminating confusing multiple readings and parallax. The font size of the digits are larger and are visible in dimly-lit environments.

**Standard DISS Outlet** – The brass, nickel-plated DISS outlet allows precise connection using standard DISS or BARB connectors.

**Service** – From on the shelf ready to ship inventory, to support with technical questions, the Spiracle team has you covered.

**Mini-Manager O<sub>2</sub> Administrator™** – Five constant flow controllers mounted to a compact, lightweight aluminum alloy manifold is ideal for mass casualty applications.

**Multi-Manager O<sub>2</sub> Administrator™** – Eight constant flow controllers mounted to a compact, lightweight aluminum alloy tripod that breaks down with quick connect bolts for compact storage and protection.

The Multi-Manager O<sub>2</sub> Administrator™ is the perfect device for oxygen delivery to multiple patients in mass casualty situations. The Multi-Manager has eight FCV's manifolded together and mounts in a collapsible tripod. The Multi-Manager can be connected in series with a second unit, increasing the number of patients treated to sixteen. In addition, standard DISS humidifiers can be connected to each FCV. The Multi-Manager requires less space to store, collapsing down to a 18" x 10" x 3" configuration.

**CAUTION: Federal law restricts this device to sale by or on the order of a physician.**

## How To Specify & Order Spiracle Technology ORO<sub>2</sub>™ Flow Control Valves

### ORO<sub>2</sub>™ FCV Model 900

12 flow settings, plus or minus 10% accuracy to reading, Off, ¼, ½, 1, 2, 3, 4, 6, 8, 10, 15, 25 liters per minute, DISS Male outlet.



### ORO<sub>2</sub>™ FCV Model 901

Same as Model # 900 except with BARB outlet



### Mini-Manager O<sub>2</sub> Administrator™ Model 905

Five model # 900 FCV's mounted on an aluminum manifold with DISS oxygen inlet. In soft carrying case.



### Multi-Manager O<sub>2</sub> Administrator™ Model 908

Eight model # 900 FCV's on an aluminum alloy tripod with DISS oxygen inlet and check valve outlet. Quick assembly and compact storage. In soft carrying case.



## Specifications

Description:	Precision, 12 flow setting, fixed orifice flow control valve. All Metal Construction
Flow Settings:	Off, ¼, ½, 1, 2, 3, 4, 6, 8, 10, 15, 25 lpm
Flow Accuracy:	¼, ½, & 1 lpm +/- 20%, other flowrates +/- 10%
Inlet pressure:	40-60 psig/3-5 bar
Materials:	2024-T4 Aluminum Alloy, Brass



**Spiracle Technology**  
A FERNO Group Company

10601 Calle Lee, #190  
Los Alamitos, CA 90720  
Phone: (714) 418-1091 • Fax: (714) 418-1095  
e-mail: info@spiracle.com • www.spiracle.com